

1300-system (C2)

# V1311C2-A

- open C-format crimp head
- fast-forward feed system
- integrated ratchet system that does not release until the crimp is complete
- fork can swivel 180°
- crimp force 130 kN
- ergonomic handle
- easy to carry and work with
- requires low handle force, approx 245 N at max force

Tested and certified hydraulic hand tool for contact crimping Cu terminals, type KRF/KSF 10-300 mm<sup>2</sup>, C-sleeves 6/6-120/120 mm<sup>2</sup>.



Item number: **5202-131400**

EAN: **7393487059733**

Fast forward function: **Yes**

Ratchet function that does not trigger until completed crimp: **Yes**

Delivery box: **Plywood box**

Working temperature, Min (°C): **-22**

Working temperature, Max (°C): **55**

Crimp geometries: **Hexagonal, Oval**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm<sup>2</sup> Cu: **10-400**

Crimp range Cu-terminals min (mm<sup>2</sup>): **10**

Crimp range Cu-terminals max (mm<sup>2</sup>): **400**

Crimp range C-connectors min (mm<sup>2</sup>): **6**

Crimp range C-connectors max (mm<sup>2</sup>): **120**



**EIPRESS**