

# DV1300

- crimp head with patented DUAL technology that gives optimised hexagonal crimping + a certain amount of indented crimping in two integrated steps
- working pressure 63 MPa (630 bar)
- crimp force 130 kN (13 tonnes)
- light and versatile steel crimp head

Crimp head with patented DUAL technology for contact crimping Cu terminals, type KRF/KSF 10-300 mm<sup>2</sup>. Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-133500**

EAN: **7393487026285**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Punch, Dual, Hexagonal, Oval**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm<sup>2</sup> Stranded Al: **16-400**

mm<sup>2</sup> Solid Al: **16-240**

mm<sup>2</sup> Cu: **10-400**

Crimp range Cu-terminals min (mm<sup>2</sup>): **10**

Crimp range Cu-terminals max (mm<sup>2</sup>): **400**

Crimp range C-connectors min (mm<sup>2</sup>): **25**

Crimp range C-connectors max (mm<sup>2</sup>): **240**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **400**

