

1300-system (H)

V1300

- working pressure 63 MPa (630 bar)
- crimp force 130 kN (13 tonnes)
- light and versatile steel crimp head

Crimp head for contact crimping Cu terminals, type KRF/KSF 10-400 mm², Al terminals 16-400 mm² (-240 solid), C sleeves 6/6-120/120 mm². Used in conjunction with foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-132500**

EAN: **7393487000520**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm² Stranded Al: **16-400**

mm² Solid Al: **16-240**

mm² Cu: **10-400**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **400**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **120**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **400**

