

KRFS tube terminals 50 - 400 mm² with narrow palm

KRFS95-12



- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- Easy to install via cable gland, allows for pre-installation.
- The width of the palm is less than or as wide as the neck.
- UL-approved, DNV approved.

Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm² 10 = palm hole for M10 F = type KRF for stranded and flexible conductors.
Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 95 mm², with an M12 hole in the palm. Used with Elpress certified systems V600, V1300, V250.



**UK
CA**

Item number: **7301-291100**
EAN: **7393487062023**

W (mm): **20**
N (mm): **12**
N1 (mm): **15**
P (mm): **27**
f (mm): **1**
d (mm): **15**
D (mm): **20**
L (mm): **64**
t (mm) - palm thickness: **5.4**
s (mm) - strip length: **25**

Screw: **M12**
Inspection hole: **Yes**

AWG/MCM Cu: **3/0 AWG**
mm² Cu: **95**

ELPRESS