

1300-system (H)

# PVX1300DB



- ergonomic design
- swivel fork
- crimp force control using pressure monitoring
- DUAL crimp technology
- fast-forward feed
- display with information about the tool and service intervals
- crimp monitoring with warning lamp (LED)
- 2 year warranty

Battery-powered crimp gun for contact crimping Cu terminals, type KRF/KSF 10-400 mm<sup>2</sup>, Al terminals 16-400 mm<sup>2</sup> (-240 solid), C sleeves 6/6-120/120 mm<sup>2</sup>. Supplied with two batteries.



Item number: **5204-011100**

EAN: **7393487061200**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Punch, Dual, Hexagonal, Oval**

Safety device: **Closed chassis**

Pressure monitoring via display: **Yes**

Work light: **Yes**

Charger: **Li-ion & Ni-MH 7.2-18V**

Charge time (min): **15**

Battery: **Li-Ion Makita, 5,0Ah, 18V**

No. of batteries: **2**

Crimp time (s): **4-12, depending on size**

Crimps/charge: **60-120 depending on size and temperature**

AWG/MCM Stranded Al: **6 AWG - 700 MCM**

AWG/MCM Solid Al: **6 AWG - 450 MCM**

AWG/MCM Cu: **8 AWG - 700 MCM**

mm<sup>2</sup> Stranded Al: **16-400**

mm<sup>2</sup> Solid Al: **16-240**

mm<sup>2</sup> Cu: **10-400**

Crimp range Cu-terminals min (mm<sup>2</sup>): **10**

Crimp range Cu-terminals max (mm<sup>2</sup>): **400**

Crimp range C-connectors min (mm<sup>2</sup>): **6x2**

Crimp range C-connectors max (mm<sup>2</sup>): **120x2**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **400**

**EIPRESS**