

600-system (6 t)

PVX611-US



Item number: **5204-012000**

EAN: **7393487061286**

Fast forward function: **Yes**

Delivery box: **Plastic case**

Working temperature, Min (°C): **-20**

Working temperature, Max (°C): **40**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Closed chassis**

Pressure monitoring via display: **Yes**

Work light: **Yes**

Charger: **Li-Ion Makita**

Charge time (min): **15**

No. of batteries: **1**

Crimp time (s): **3-6, depending on size**

Crimps/charge: **100-200 depending on size and temperature**

AWG/MCM Stranded Al: **6 - 4 AWG**

AWG/MCM Solid Al: **6 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm² Stranded Al: **16-25**

mm² Solid Al: **16-35**

mm² Cu: **10-240**

mm² KR/KS, KRF/KSF: **10-150**

mm² KRT/KST: **10-240**

mm² KRD/KSD: **16-185**

Crimp range Cu-terminals min (mm²): **10**

Crimp range Cu-terminals max (mm²): **240**

Crimp range C-connectors min (mm²): **6**

Crimp range C-connectors max (mm²): **50**

Crimp range Al-terminals min (mm²): **16**

Crimp range Al-terminals max (mm²): **25**



