

# KRF185-10

- Material: Cu 99.95%, tin plated Cu/Sn.
- With inspection holes.
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- UL-approved, DNV approved.



## Example of marking KRF: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die No. 70 = mm<sup>2</sup> 10 = palm hole for M10 F =  
type KRF for stranded and flexible conductors.

Tube terminal for multi-stranded (class 5) and  
stranded wire (class 2) Cu conductors (acc. to IEC  
60228), 185 mm<sup>2</sup>, with an M10 hole in the palm.

Used with Elpress certified systems V1300 or V250.



**UK  
CA**

Item number: **7301-030300**

EAN: **7393487006553**

W (mm): **39**

N (mm): **15**

N1 (mm): **16**

P (mm): **31**

f (mm): **1**

d (mm): **21**

D (mm): **27**

L (mm): **86**

t (mm) - palm thickness: **5.9**

s (mm) - strip length: **37**

Screw: **M10**

Inspection hole: **Yes**

AWG/MCM Cu: **350 MCM**

mm<sup>2</sup> Cu: **185**