

600-system (6 t)

# V600

- same crimp dies as V611 and PVX611
- crimp force 55 kN
- delivered in sturdy fabric bag with room for 10 dies

Crimp head for contact crimping of Cu terminals, type, KRF/KSF 10-150 mm<sup>2</sup>, Al terminals 16-25 mm<sup>2</sup> (-35 solid), C-sleeves 6/6-50/50 mm<sup>2</sup>. Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-060000**

EAN: **7393487037342**

Delivery box: **Textile bag**

Crimp geometries: **Punch, Hexagonal, Oval**

Working pressure (MPa): **63**

AWG/MCM Stranded Al: **6 - 4 AWG**

AWG/MCM Solid Al: **6 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm<sup>2</sup> Stranded Al: **16-25**

mm<sup>2</sup> Solid Al: **16-35**

mm<sup>2</sup> Cu: **10-240**

mm<sup>2</sup> KR/KS, KRF/KSF: **10-150**

mm<sup>2</sup> KRT/KST: **10-240**

mm<sup>2</sup> KRD/KSD: **16-185**

Crimp range C-connectors min (mm<sup>2</sup>): **6/6**

Crimp range C-connectors max (mm<sup>2</sup>): **50/50**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **25**



**EIPRESS**