

V1470-system (40 t)

# V1470

- fitted with safety device in the form of a protective cover and with quick coupler
- working pressure 63 MPa (630 bar)
- crimp force 400 kN
- supplied in plywood box

Tested and certified crimp head for crimping Cu-terminals 500-1000 mm<sup>2</sup>, Al-terminals 800-1200 mm<sup>2</sup>, C-sleeves 245-600 mm<sup>2</sup>. Used in conjunction with Elpress foot pump P4000 or battery and mains powered pump PS710.



Item number: **5208-404000**

EAN: **7393487000568**

Delivery box: **Plywood box**

Crimp geometries: **Punch, Hexagonal, Oval**

Safety device: **Protective cover**

Working pressure (MPa): **63**

Quick connector: **Yes**

AWG/MCM Stranded Al: **1600 - 2500 MCM**

AWG/MCM Cu: **1000 - 2000 MCM**

mm<sup>2</sup> Stranded Al: **800-1200**

mm<sup>2</sup> Cu: **500-1000**

Crimp range Cu-terminals min (mm<sup>2</sup>): **500**

Crimp range Cu-terminals max (mm<sup>2</sup>): **1000**

Crimp range C-connectors min (mm<sup>2</sup>): **150**

Crimp range C-connectors max (mm<sup>2</sup>): **300**

Crimp range Al-terminals min (mm<sup>2</sup>): **800**

Crimp range Al-terminals max (mm<sup>2</sup>): **1200**

