

600-system (6 t)

# V611



- fast-feed to crimp engagement provides short crimp times
- same crimp dies as for V600 and PVX611
- crimp force 55 kN

Tested and certified hydraulic hand tool for contact crimping Cu terminals type KRF/KSF 10-150 mm<sup>2</sup>, Al terminals 16-25 mm<sup>2</sup> (-35 solid), C-sleeves 6/6-50/50 mm<sup>2</sup>.



Item number: **5202-001600**

EAN: **7393487026971**

Fast forward function: **Yes**

Delivery box: **Plastic case**

Crimp geometries: **Punch, Hexagonal, Oval**

AWG/MCM Stranded Al: **6 - 4 AWG**

AWG/MCM Solid Al: **6 - 2 AWG**

AWG/MCM Cu: **18 - 10 AWG**

mm<sup>2</sup> Stranded Al: **16-25**

mm<sup>2</sup> Solid Al: **16-35**

mm<sup>2</sup> Cu: **10-240**

mm<sup>2</sup> KR/KS, KRF/KSF: **10-150**

mm<sup>2</sup> KRT/KST: **10-240**

mm<sup>2</sup> KRD/KSD: **16-185**

Crimp range C-connectors min (mm<sup>2</sup>): **6/6**

Crimp range C-connectors max (mm<sup>2</sup>): **50/50**

Crimp range Al-terminals min (mm<sup>2</sup>): **16**

Crimp range Al-terminals max (mm<sup>2</sup>): **25**