

KRFS tube terminals 50 - 400 mm<sup>2</sup> with narrow palm

# KRFS240A- 12

- Material: Cu 99.95%, tin plated Cu/Sn.
- Inspection hole
- For stranded (class 2) and multi-stranded (class 5) Cu conductors, for multi-stranded Cu conductors contact crimping using the Dual system is recommended.
- Easy to install via cable gland, allows for pre-installation.
- The width of the palm is less than or as wide as the neck.

## Example of marking KRFS: 17 (neck) Elpress logotype 70 10F (palm)

17 = Die no. 70 = mm<sup>2</sup> 10 = palm hole for M10 F = type KRF for stranded and flexible conductors. Tube terminal with narrow palm for multi-stranded (class 5) and stranded (class 2) Cu conductors (acc. to IEC 60228), 240 mm<sup>2</sup>, with an M12 hole in the palm. Used with Elpress certified systems V1300 or V250.



Item number: **7301-292600**

EAN: **7393487062146**

W (mm): **29**

N (mm): **15**

N1 (mm): **19**

P (mm): **34**

f (mm): **1**

d (mm): **22.5**

D (mm): **29**

L1 (mm): **76**

L (mm): **91**

t (mm) - palm thickness: **7.7**

s (mm) - strip length: **37**

Screw: **M12**

Inspection hole: **Yes**

AWG/MCM Cu: **450 MCM**  
mm<sup>2</sup> Cu: **240**

